

### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Issue date: 6/15/2023 Revision date: 6/15/2023 Version: 1.00

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture
Name : Bedliner - Black

Trade name : COBRA SPRAY 2K DTM :

Vaporizer Aeroso

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : The product is intended for professional use

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

NOVOL Sp. z o.o. Żabikowska 7/9 62-052 KOMORNIKI Poland

T 0048618109800 - F 0048618109809

www.novol.com

E-mail address of competent person responsible for the SDS: dokumentacja@novol.com

Imported By ALTREX AUTO ACCESSORIES D31, 148 Old Pittwater Road Brookvale NSW 2100 Tel 02 9905 5055

#### 1.4. Emergency telephone number

Emergency number : 112 Australian Emergency Contact Poison Information Hotline 131 126

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Acute toxicity (inhalation:dust,mist) Category 4 H332
Skin corrosion/irritation, Category 2 H315
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

No additional information available

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP):





GHS02 GHS07

Signal word (CLP)

Contains

Hazard statements (CLP)

: Danger : xylene; dimethyl ether

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

### Safety Data Sheet

Precautionary statements (CLP)

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

H332 - Harmful if inhaled.

H412 - Harmful to aquatic life with long lasting effects.

: P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P260 - Do not breathe vapours, spray.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

P312 - Call doctor if you feel unwell.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122

°F.

: EUH204 - Contains isocyanates. May produce an allergic reaction.

**EUH-statements** 

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00- 9 REACH-no: 01- 2119488216-32	< 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
dimethyl ether substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit (Note U)	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00- 8 BFAらわり9ン81-	< 25	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
acetone substance with national workplace exposure limit(s) (GB); substance with a Community workplace exposure limit	37 CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-	<10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hexamethylen-1,6-Diisocyanat Homopolimer	BEACH-ng: 01- 2119471330- 49 CAS-No.: 28182-81-2	<10	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
trizinc bis(orthophosphate)	EC-No.: 500-060-2 REACH-no: 01- 2119485796- 17 CAS-No.: 7779-90-0	< 2.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

EC-No.: 231-944-3 EC Index-No.: 030-011-00-

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier		Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate CAS-No.: 123-86-4 < 1 Flam. Liq. 3, H22 substance with national workplace exposure limit(s) EC- (GB); substance with a Community workplace EC Index- exposure limit REACH-no: 01-2119485493- 29	No.: 204-658-1 STOT SE 3, H33	86	

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:. Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general : General information. Refer to section 11.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing.

First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash

immediately with plenty of water and soap. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If skin irritation continues, consult a doctor.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. Call a physician immediately. In case of contact with eyes, rinse

immediately with plenty of water and seek medical advice.

First-aid measures after ingestion : If swallowed: rinse mouth. Do NOT induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Vapours may cause drowsiness and dizziness.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry. :

Symptoms/effects after eye contact May cause eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO2, alcohol-resistant foam or waterspray. :

Unsuitable extinguishing media Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Carbon monoxide. Other toxic gases.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment

: Remove ignition sources. Ensure that there is a suitable ventilation system. Avoid any direct or indirect contact with ingredients released. Avoid contact with skin and eyes. Use personal protective equipment as required. See Section 8.

#### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. See Section 8.

#### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

### 6.3. Methods and material for containment and cleaning up

For containment

: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Mechanically recover the product.

#### 6.4. Reference to other sections

Disposal considerations. See Section 13.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling

: Pressurized container. Do not spray on an open flame or other ignition source. Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Ground/bond container and receiving equipment.

Storage conditions

: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from ignition sources. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep out of reach of children.

### 7.3. Specific end use(s)

No additional information available

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### 8.1.1 National occupational exposure and biological limit values

acetone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name Acetone	
IOEL TWA [ppm] 500 ppm	
Regulatory reference COMMISSION DIRECTIVE 2000/3	99/EC

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

acetone (67-64-1)		
United Kingdom - Occupational Exposure Limits		
Local name	Acetone	
WEL TWA (OEL TWA) [1]	1210 mg/m³	
WEL TWA (OEL TWA) [2]	500 ppm	
WEL STEL (OEL STEL)	3620 mg/m³	
WEL STEL (OEL STEL) [ppm]	1500 ppm	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
n-butyl acetate (123-86-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name n-Butyl acetate		
IOEL TWA [ppm] 50 ppm		
IOEL STEL 723 mg/m³		
IOEL STEL [ppm] 150 ppm		
Regulatory reference COMMISSION DIRECTIVE (EU)	2019/1831 United Kingdom - Occupational	
Exposure Limits		
Local name Butyl acetate		
WEL TWA (OEL TWA) [1] 724 mg/m³		
WEL TWA (OEL TWA) [2] 150 ppm		
WEL STEL (OEL STEL) 966 mg/m³		
WEL STEL (OEL STEL) [ppm] 200 ppm		
Regulatory reference EH40/2005 (Fourth edition, 2020	). HSE	
Fularia (4220-20 E)		
xylene (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name Xylene, mixed isomers, pure		
IOEL TWA [ppm] 50 ppm		
IOEL STEL 442 mg/m³		
IOEL STEL [ppm] 100 ppm		
Remark Skin		
Regulatory reference COMMISSION DIRECTIVE 2000/	39/EC	
United Kingdom - Occupational Exposure Limits		
Local name Xylene		
WEL TWA (OEL TWA) [1] 220 mg/m³ o-,m-,p- or mixed	somers	
WEL TWA (OEL TWA) [2] 50 ppm o-,m-,p- or mixed ison	ners	
WEL STEL (OEL STEL) 441 mg/m³ o-,m-,p- or mixed isc	mers	
WEL STEL (OEL STEL) [ppm] 100 ppm o ,m-,p- or mixe	# isomers	
Remark Sk (Can be absorbed through the skin. The ass		
are concerns that dermal absorption will lead to system Regulatory reference EH40/2005 (Fourth edition, 2020)		

### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

xylene (1330-20-7)	
xyterie (1330-20-7)	
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
dimethyl ether (115-10-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name Dimethylether	
IOEL TWA [ppm] 1000 ppm	
Regulatory reference COMMISSION DIRECTIVE 2000,	39/EC United Kingdom - Occupational
Exposure Limits	
Local name Dimethyl ether	
WEL TWA (OEL TWA) [1] 766 mg/m³	
WEL TWA (OEL TWA) [2] 400 ppm	
WEL STEL (OEL STEL) 958 mg/m³	
WEL STEL (OEL STEL) [ppm] 500 ppm	
Regulatory reference EH40/2005 (Fourth edition, 2020)	. HSE
8.1.2. Recommended monitoring procedures	

Monitoring methods	
I = = = = = = = = = = = = = = = = = = =	EN 482. Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents.

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

## 8.2.2. Personal protection equipment

### Personal protective equipment symbol(s):







### 8.2.2.1. Eye and face protection

### Eye protection:

Safety glasses

### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### **Hand protection:**

Protective gloves

#### **Hand protection**

Type Material Permeation	Type Material Permeation				
Disposable gloves Viton® II 6 (	(> 480 minutes)		Thickness (mm)	Penetration	Standard
Disposable gloves Nitrile rubb	er (NBR) 2 (> 30 minutes)		0,7 mm		EN 374-3
8.2.2.3. Respiratory protection	on		0,4 mm		EN 374-3

#### **Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment

#### **Respiratory protection**

Device Filter type		
Gas mask with filter type Filter A1/B1	Condition	Standard
8.2.2.4. Thermal hazards		EN 14387

No additional information available

### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Black. : Aerosol Appearance Odour : characteristic. Odour threshold : Not available Melting point : Not applicable : Not available Freezing point : ≈ -25 °C **Boiling point** : Not applicable Flammability Explosive properties : No data available. Explosive limits : Not available : 1.1 vol % Lower explosion limit Upper explosion limit : 18.6 vol %

Flash point :  $\approx$  -42 °C Not applicable :

Auto-ignition temperature Not applicable : Not available Decomposition temperature : Not available рΗ Viscosity, kinematic : Not available Solubility : Slightly soluble. Partition coefficient n-octanol/water (Log : Not available Kow) Vapour pressure : 3500 hPa Vapour pressure at 50°C : Not available : 0.8 g/cm3 Density : Not available Relative density Relative vapour density at 20°C : Not available Particle characteristics : Not applicable

### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : < 90 %

#### 9.2.2. Other safety characteristics

No additional information available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Prevent build-up of electrostatic charges (e.g, by grounding).

#### 10.5. Incompatible materials

No contact with: strong acids, strong bases and strong oxidants.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce: Carbon monoxide. Other toxic gases.

### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met) : Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met) : Acute toxicity (inhalation) : Harmful if inhaled.

, water to morely (minutation)	
COBRA SPRAY 2K DTM	
ATE CLP (dust,mist)	4.286 mg/l/4h
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
n-butyl acetate (123-86-4)	
LD50 oral rat	12.2 ml/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 4.9 mg/l Source: ECHA
trizinc bis(orthophosphate) (7779-90-0)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

trizinc bis(orthophosphate) (7779-90	P-0)
LC50 Inhalation - Rat	> 5700 mg/m³ Source: ECHA
xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg rat
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex:
LC50 Inhalation - Rat	male 27124 mg/l
dimethyl ether (115-10-6)	
LC50 Inhalation - Rat	308.5 mg/l Source: International Uniform ChemicaL Information
LC50 Inhalation - Rat [ppm]	Database 164000 ppm Animal: rat, Animal sex: male, 95% CL: 142000 -
Hexamethylen-1,6-Diisocyanat Hom	opolimer (28182081-2)
LD50 oral rat	> 2500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:
Skin corrosion/irritation	: Causes skin irritation.
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
рН	6.2 Temp.: 20 °C Concentration: 5,3 g/L
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
acetone (67-64-1)	: Not classified (Based on available data, the classification criteria are not met)
acetone (07-04-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	•
STOT-single exposure	May cause drowsiness or dizziness.
Hexamethylen-1,6-Diisocyanat Hom	opolimer (28182-81-2)
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
n-butyl acetate (123-86-4)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

trizinc bis(orthophosphate) (7779-90	0-0)
LOAEL (oral, rat, 90 days)	53.8 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity Study in Rodents)
xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
COBRA SPRAY 2K DTM	
Vaporizer	Aerosol
n-butyl acetate (123-86-4)	
Viscosity, kinematic	0.83 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

### 11.2. Information on other hazards

No additional information available

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute)

d to----

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic)

: Harmful to aquatic life with long lasting effects.

Not rapidly degradable

Not rapidly degradable	
acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l Source: ECHA
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Source: ECHA
EC50 - Crustacea [1]	44 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	32 mg/l Test organisms (species): Artemia salina
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum) 47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	
xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia

### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

xylene (1330-20-7)				
NOEC chronic fish > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salm gairdneri) Duration: '56 d'				
dimethyl ether (115-10-6)				
LC50 - Fish [1]	> 4.1 g/l Test organisms (species): Poecilia reticulata			
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna			
EC50 96h - Algae [1] 154.917 mg/l Test organisms (species): other:green algae				
Hexamethylen-1,6-Diisocyanat Homopolimer (28182-81-2)				
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): other:			

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

acetone (67-64-1)			
Partition coefficient n-octanol/water (Log Pow) -0.24 Source: ICSC			
n-butyl acetate (123-86-4)			
Partition coefficient n-octanol/water (Log Pow) 1.78 Source: HSDB			
dimethyl ether (115-10-6)			
Partition coefficient n-octanol/water (Log Pow)  0.1 Source: International Chemical Safety Cards			

### 12.4. Mobility in soil

dimethyl ether (115-10-6)	
Mobility in soil	27 Source: National Library of Medicine/Hazardous Substances Data Bank

#### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Regional legislation (waste)

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

European List of Waste (LoW) code

- : Disposal must be done according to official regulations.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Do not discharge into drains.
- : This material and its container must be disposed of as hazardous waste. Do not dispose of with domestic waste. After cleaning, recycle or dispose of at an authorised site.
- : Flammable vapours may accumulate in the container.  $\,$
- : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

15 01 10\* - packaging containing residues of or contaminated by dangerous substances

### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA		
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950		
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable		
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1 (-42°C c.c.)	UN 1950 Aerosols, flammable, 2.1		
14.3. Transport hazard class(es)				
2.1	2.1	2.1		
2				
14.4. Packing group				
Not applicable	Not applicable	Not applicable		
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No		
No supplementary information available	•			

### 14.6. Special precautions for user

### **Overland transport**

Classification code (ADR) : 5F Limited quantities (ADR) : 1l

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR): MP9Transport category (ADR): 2Special provisions for carriage - Packages (ADR): V14

Tunnel restriction code (ADR) : D

### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959 Limited quantities (IMDG) : SP277

Elmited quantities (IMDG)

Special packing provisions (IMDG)

EmS-No. (Fire)

EmS-No. (Spillage)

Stowage category (IMDG)

Stowage and handling (IMDG)

Segregation (IMDG)

SG69

### Air transport

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **ANNEX II REPORTABLE EXPLOSIVES PRECURSORS**

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Nomenclature	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone 67-64-1 2914 1	1 00 ex 3824 99 92		

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list\_of\_competent\_authorities\_and\_national\_contact\_points\_en.pdf

### **Drug Precursors Regulation (273/2004)**

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

#### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

#### **SECTION 16: Other information**

### **Indication of changes:**

SDS EU format according to COMMISSION REGULATION (EU) 2020/878.

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE Acute Toxicity Estimate		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations a	Abbreviations and acronyms:		
BCF	Bioconcentration factor		
BLV	Biological limit value		
BOD	Biochemical oxygen demand (BOD)		
COD	Chemical oxygen demand (COD)		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
<del>IMDG</del>	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAFC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
voc	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		
ED	Endocrine disrupting properties		
Data assures	FCHA (Furnana Chaminala Agana)		
Data sources Training advice	: ECHA (European Chemicals Agency). : Handle in accordance with good industrial hygiene and safety procedures.		

: Handle in accordance with good industrial hygiene and safety procedures.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation) Acute toxicity (inhal.), Category 4		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EU	H-statements:
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH204	Contains isocyanates. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H <del>226</del>	Flammable liquid and vapour.
H <del>229</del>	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H312	Harmful in contact with skin.
H <del>315</del>	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:			
Aerosol 1 H222;H229 Acute Tox. 4	On basis of test data		
H332 (Inhalation:dust,mist)	Calculation method		
Skin Irrit. 2 H315	Calculation method		
Skin Sens. 1 H317	Calculation method		
Aquatic Chronic 3 H412	Calculation method		

Safety Data Sheet (SDS), EU

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.